



# MICHELIN AGRIBIB

**HIGH PERFORMANCE  
WITH OPTIMAL TRACTION**



### FOR TRACTORS UP TO 220 HP

and up to 500 HP with dual and triple fitments (42", 46", 50")



### OPTIMAL TRACTION

- Maintains traction throughout its life, even when worn



### EXCELLENT SERVICE LIFE thanks to deep tread lugs



### ROBUSTNESS

- Proven radial casing endurance
- Damage-resistant rubber

## SIZES

9.5R24 112A8/109B TL

11.2R24 119A8/116B TL

12.4R24 119A8/116B TL

13.6R24 124A8/121B TL

14.9R24 130A8/127B TL

16.9R24 134A8/131B TL

12.4R28 126A8/123B TL

13.6R28 123A8/120B TL

14.9R28 134A8/131B TL

16.9R28 141A8/138B TL

380/85R30 135A8/135B TL

16.9R30 137A8/134B TL

420/90R30 147A8/147B TL

18.4R30 142A8/139B TL

320/85R34 133A8/130B TL

380/85R34 137A8/137B TL

420/85R34 147A8/147B TL

18.4R34 149A8/146B TL

12.4R36 124A8/121B TL

12.4R38 131A8/128B TL

13.6R38 128A8/125B TL

420/85R38 144A8/144B TL

380/95R38 147A8/147B TL

18.4R38 151A8/148B TL

20.8R38 159A8/156B TL

520/85R38 155A8/155B TL

480/80R42 156A8/156B TL

520/85R42 157A8/157B TL

420/80R46 151A8/148B TL

480/80R46 158A8/158B TL

520/85R46 158A8/155B TL

480/80R50 159A8/159B TL

480/95R50 164A8/164B TL

# MICHELIN AGRIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>24</b>	<b>9.5R24 112A8/109B TL</b>	200987	253	1045	481	3117	W8		W7		686	65	32
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>	<b>30</b>	<b>33</b>	<b>35</b>
10 km/h	675	745	815	960	1100	1240	1280	1315	1395	1475	1515	1595	1635
30 km/h	535	605	675	745	815	885	965	1045	1105	1170	1200		
40 km/h			630	695	760	825	900	975	1035	1090	1120		
40 km/h Dual	385	470	555	615	675	740	800	860	910	960	985		
50 km/h			575	640	710	775	830	885	940	995	1020		

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>24</b>	<b>11.2R24 119A8/116B TL</b>	317247	288	1095	503	3269	W10		W9		692	92	37
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>	<b>30</b>	<b>33</b>	<b>35</b>
10 km/h	840	925	1005	1170	1335	1500	1570	1635	1720	1810	1850	1935	1980
30 km/h	660	745	830	910	990	1070	1170	1265	1340	1415	1455		
40 km/h			775	850	925	1000	1090	1180	1250	1325	1360		
40 km/h Dual	480	580	680	750	825	895	970	1040	1100	1165	1195		
50 km/h			705	780	860	935	1005	1075	1140	1205	1240		

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>24</b>	<b>12.4R24 119A8/116B TL</b>	123788	324	1149	520	3420	W11		W10		692	116	41
<b>Bar</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>					
<b>Psi</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>					
10 km/h	1040	1200	1330	1460	1590	1715	1845	1975					
30 km/h	810	950	1050	1155	1255	1360	1460						
40 km/h		880	975	1070	1170	1265	1360						
50 km/h		830	915	1000	1080	1165	1250						

\* Refer to the notes at the end of the tables of this range

# MICHELIN AGRIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>24</b>	<b>13.6R24 124A8/121B TL</b>	262831	370	1200	551	3583	W12		W11		700	144	43	
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	<b>2.6</b>
<b>Psi</b>	6	7	9	12	15	17	20	23	26	29	30	33	35	38
10 km/h	975	1075	1175	1375	1570	1770	1850	1930	2030	2130	2175	2275	2325	
30 km/h	760	865	965	1065	1165	1265	1385	1500	1585	1670	1710			
40 km/h			900	995	1085	1180	1290	1400	1480	1560	1600			
40 km/h Dual	555	675	790	880	965	1055	1140	1230	1300	1375	1410			
40 km/h FRT								1550	1680	1775	1825	1920	1960	2040
50 km/h		820	915	1010	1105	1190	1275	1345	1420	1455				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>24</b>	<b>14.9R24 130A8/127B TL</b>	601563	397	1265	575	3769	W13		W11 W12		703	188	48	
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	
<b>Psi</b>	6	7	9	12	15	17	20	23	26	29	30	33	35	
10 km/h	1165	1280	1400	1635	1865	2100	2175	2250	2380	2515	2580	2710	2775	
30 km/h	910	1040	1165	1275	1390	1500	1635	1765	1875	1980	2035			
40 km/h			1090	1195	1295	1400	1525	1650	1750	1850	1900			
40 km/h Dual	660	810	960	1060	1155	1255	1350	1450	1540	1625	1670			
50 km/h		990	1100	1210	1320	1410	1500	1590	1685	1730				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>24</b>	<b>16.9R24 134A8/131B TL</b>	123854	460	1330	586	3935	DW15L		DW14L W14L W15L		710	244	55	
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>					
<b>Psi</b>	6	7	9	12	15	17	20	23	26					
10 km/h		1620	1880	2080	2280	2480	2680	2880	3080					
30 km/h		1270	1470	1630	1790	1950	2110	2270						
40 km/h			1380	1530	1675	1825	1970	2120						
40 km/h Dual	790	1005	1215	1345	1475	1605	1735	1865						
50 km/h		1290	1420	1555	1685	1820	1950							

\* Refer to the notes at the end of the tables of this range

# MICHELIN AGRIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>28</b>	<b>12.4R28 126A8/123B TL</b>	738964	322	1265	586	3778	W11		W10		726	134	40
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>	<b>30</b>	<b>33</b>	<b>35</b>
10 km/h	1035	1140	1245	1455	1665	1875	1960	2040	2150	2260	2310	2420	2475
30 km/h	805	925	1045	1145	1240	1340	1475	1605	1690	1775	1820		
40 km/h			975	1065	1160	1250	1375	1500	1580	1660	1700		
40 km/h Dual	590	725	860	950	1045	1135	1230	1320	1390	1460	1495		
50 km/h			885	980	1075	1170	1270	1365	1435	1510	1545		

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>28</b>	<b>13.6R28 123A8/120B TL</b>	123782	372	1308	592	3893	W12		W11		732	173	46
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>	<b>30</b>	<b>33</b>	<b>35</b>
10 km/h		1190	1370	1520	1665	1815	1960	2110	2255				
30 km/h		930	1080	1195	1310	1430	1545	1660					
40 km/h			1010	1120	1225	1335	1440	1550					
40 km/h Dual	590	740	890	985	1080	1175	1270	1365					
50 km/h		920	1015	1110	1210	1305	1400						

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
<b>28</b>	<b>14.9R28 134A8/131B TL</b>	112235	393	1365	624	4072	W13		W12		821	210	47		
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>	<b>30</b>	<b>33</b>	<b>35</b>	<b>38</b>	<b>41</b>
10 km/h	1240	1365	1495	1745	2000	2250	2365	2475	2625	2775	2825	2925	2980	3080	3180
30 km/h	885	980	1070	1230	1420	1605	1765	1925	2010	2100	2140	2225	2270		
40 km/h			1000	1150	1325	1500	1650	1800	1880	1960	2000	2080	2120		
50 km/h			910	1045	1205	1365	1505	1640	1715	1785	1820	1895	1930		

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
<b>28</b>	<b>16.9R28 141A8/138B TL</b>	984997	454	1435	655	4278	DW15L		DW14L W14L W15L		822	272	51		
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>	<b>30</b>	<b>33</b>	<b>35</b>	<b>38</b>	<b>41</b>
10 km/h	1500	1650	1800	2100	2400	2700	2850	3000	3180	3360	3425	3550	3615	3740	3865
30 km/h	1070	1185	1300	1500	1715	1925	2130	2335	2440	2545	2600	2705	2755		
40 km/h			1215	1400	1600	1800	1990	2180	2280	2380	2425	2525	2575		
50 km/h			1105	1275	1460	1640	1815	1985	2075	2165	2210	2300	2345		

\* Refer to the notes at the end of the tables of this range

# MICHELIN AGRIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>30</b>	<b>380/85R30 135A8/135B TL</b>	836509	386	1416	628	4194	W12	W13	734	209	46
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>		
<b>Psi</b>	6	7	9	12	15	17	20	23	26		
10 km/h	1450	1565	1680	1905	2135	2360	2580	2800	3100		
30 km/h	1060	1155	1250	1450	1675	1900	2100	2300			
40 km/h			1180	1360	1555	1750	1965	2180			
40 km/h Dual	860	950	1040	1195	1370	1540	1730	1920			
50 km/h			1180	1360	1550	1750	1965	2180			

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>30</b>	<b>16.9R30 137A8/134B TL</b>	123870	447	1480	664	4395	DW15L	DW14L W14L W15L	754	285	49
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>		
<b>Psi</b>	6	7	9	12	15	17	20	23	26		
10 km/h		1760	2040	2255	2475	2690	2910	3125	3340		
30 km/h		1380	1600	1770	1945	2115	2290	2460			
40 km/h			1500	1660	1820	1980	2140	2300			
40 km/h Dual	880	1100	1320	1460	1600	1745	1885	2025			
50 km/h			1400	1545	1690	1830	1975	2120			

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)				
<b>30</b>	<b>420/90R30 147A8/147B TL</b>	953332	443	1533	690	4556	DW13	W13 DW14L W14L	754	284	44				
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>
<b>Psi</b>	6	7	9	12	15	17	20	23	26	29	30	33	35	38	41
10 km/h	1800	1955	2110	2415	2725	3035	3340	3650	3950	4250	4315	4440	4500	4565	4625
30 km/h	1285	1420	1550	1800	2050	2300	2550	2800	2940	3075	3145	3280	3350		
40 km/h			1450	1700	1940	2175	2415	2650	2775	2900	2945	3030	3075		
40 km/h Dual	1070	1175	1275	1495	1705	1915	2120	2330	2440	2550	2590	2665	2705		
50 km/h			1450	1700	1940	2175	2415	2650	2775	2900	2945	3030	3075		

\* Refer to the notes at the end of the tables of this range

# MICHELIN AGRIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>30</b>	<b>18.4R30 142A8/139B TL</b>	123844	504	1550	695	4602	DW16L	DW15L W15L W16L	757	353	54
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>		
<b>Psi</b>	6	7	9	12	15	17	20	23	26		
10 km/h		2030	2350	2600	2850	3100	3355	3605	3855		
30 km/h		1590	1840	2040	2240	2440	2640	2840			
40 km/h			1720	1905	2090	2280	2465	2650			
40 km/h Dual	1040	1280	1515	1680	1840	2005	2165	2330			
50 km/h		1600	1765	1930	2100	2265	2430				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)				
<b>34</b>	<b>320/85R34 133A8/130B TL</b>	122760	320	1420	651	4239	W10			155	39				
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>
<b>Psi</b>	6	7	9	12	15	17	20	23	26	29	30	33	35	38	41
10 km/h	1215	1315	1410	1610	1805	2000	2215	2430	2615	2800	2835	2905	2940	3005	3075
30 km/h	850	940	1030	1215	1385	1550	1725	1900	1980	2060	2090	2150	2180		
40 km/h			975	1120	1285	1450	1600	1750	1850	1950	1980	2035	2060		
40 km/h Dual	705	785	860	985	1130	1275	1410	1540	1630	1715	1740	1790	1815		
50 km/h			900	1030	1180	1320	1460	1600	1700	1800	1825	1875	1900		

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>34</b>	<b>380/85R34 137A8/137B TL</b>	122781	394	1503	673	4461	W12	W13	704	230	44
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>		
<b>Psi</b>	6	7	9	12	15	17	20	23	26		
10 km/h	1550	1670	1790	2025	2265	2500	2750	3000	3300		
30 km/h	1120	1220	1320	1550	1775	2000	2215	2430			
40 km/h			1250	1450	1650	1850	2075	2300			
40 km/h Dual	905	1005	1100	1275	1455	1630	1830	2025			
50 km/h			1250	1450	1650	1850	2075	2300			

\* Refer to the notes at the end of the tables of this range

# MICHELIN AGRIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)			
<b>34</b>	<b>420/85R34 147A8/147B TL</b>	788910	455	1595	725	4751	DW15L		W13 DW14L W14L W15L	704	287	51			
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>	<b>30</b>	<b>33</b>	<b>35</b>	<b>38</b>	<b>41</b>
10 km/h	1800	1940	2075	2350	2625	2900	3175	3450	3800	4045	4115	4260	4330	4475	4615
30 km/h	1300	1430	1560	1815	2075	2330	2585	2835	2950	3065	3120	3235	3290		
40 km/h			1450	1695	1935	2180	2415	2650	2755	2865	2915	3020	3075		
40 km/h Dual			1280	1495	1705	1920	2125	2330	2425	2520	2570	2665	2710		
50 km/h			1450	1695	1935	2180	2415	2650	2755	2865	2915	3020	3075		

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)			
<b>34</b>	<b>18.4R34 149A8/146B TL</b>	679786	491	1662	747	4940	DW16L		DW15L W15L W16L	823	395	54			
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>		
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>	<b>30</b>	<b>33</b>	<b>35</b>		
10 km/h	1980	2175	2370	2760	3150	3540	3705	3865	4080	4295	4405	4620	4725		
30 km/h	1550	1765	1980	2160	2345	2525	2760	2995	3190	3385	3480				
40 km/h			1850	2020	2190	2360	2580	2800	2980	3160	3250				
40 km/h Dual	1130	1380	1630	1795	1965	2130	2300	2465	2625	2780	2860				
50 km/h			1685	1860	2035	2210	2380	2550	2715	2880	2960				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>36</b>	<b>12.4R36 124A8/121B TL</b>	123952	318	1460	673	4363	W11		W10	779	165	33
<b>Bar</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>				
<b>Psi</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>				
10 km/h	1220	1420	1570	1720	1870	2025	2175	2325				
30 km/h	960	1110	1230	1350	1470	1590	1710					
40 km/h			1040	1150	1265	1375	1490	1600				
50 km/h			960	1060	1155	1255	1350	1450				

\* Refer to the notes at the end of the tables of this range

# MICHELIN AGRIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>38</b>	<b>12.4R38 131A8/128B TL</b>	258138	325	1500	697	4484	<b>W11</b>		<b>DW10 W10</b>	779	165	35	
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>	<b>30</b>	<b>33</b>	<b>35</b>
10 km/h	1200	1315	1425	1650	1875	2100	2215	2325	2440	2550	2605	2720	2775
30 km/h	935	1070	1200	1300	1400	1500	1660	1820	1925	2030	2085		
40 km/h			1120	1215	1305	1400	1550	1700	1800	1900	1950		
40 km/h Dual	680	835	985	1085	1190	1290	1395	1495	1585	1670	1715		
50 km/h			1020	1120	1220	1320	1435	1545	1635	1730	1775		

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>38</b>	<b>13.6R38 128A8/125B TL</b>	123992	358	1565	722	4705	<b>DW12</b>		<b>W11 W12</b>	795	218	45
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>			
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>			
10 km/h		1380	1590	1760	1930	2100	2275	2445	2615			
30 km/h		1080	1250	1385	1520	1660	1795	1930				
40 km/h			1030	1140	1250	1365	1475	1585				
40 km/h Dual	685	860	1030	1140	1250	1365	1475	1585				
50 km/h			1090	1200	1315	1425	1540	1650				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>38</b>	<b>420/85R38 144A8/144B TL</b>	607820	455	1676	750	4975	<b>DW15L</b>		<b>DW14L W14L W15L</b>	786	311	51
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>			
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>			
max 40 km/h FRT					2160	2460	2760	3060	3360			
10 km/h	1900	2045	2190	2485	2775	3065	3360	3650	4015			
30 km/h	1375	1510	1645	1915	2190	2460	2730	3000				
40 km/h			1550	1800	2050	2300	2550	2800				
40 km/h Dual	1130	1240	1355	1575	1800	2020	2245	2465				
50 km/h			1550	1800	2050	2300	2550	2800				

\* Refer to the notes at the end of the tables of this range



# MICHELIN AGRIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
<b>38</b>	<b>380/95R38 147A8/147B TL</b>	836033	392	1689	769	5034	W12		W13		795	286	47		
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>
<b>Psi</b>	6	7	9	12	15	17	20	23	26	29	30	33	35	38	41
10 km/h	1825	1980	2130	2440	2745	3055	3360	3670	3975	4100	4165	4295	4355	4485	4610
30 km/h	1300	1430	1555	1810	2070	2325	2580	2835	2950	3065	3120	3235	3290		
40 km/h			1450	1690	1930	2170	2410	2650	2755	2865	2915	3020	3075		
40 km/h Dual	1070	1150	1235	1395	1560	1725	1890	2050	2215	2380	2460	2625	2705		
50 km/h			1450	1690	1930	2170	2410	2650	2755	2865	2915	3020	3075		

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
<b>38</b>	<b>18.4R38 151A8/148B TL</b>	100097	494	1770	800	5267	DW16L		DW15L W15L W16L		824	431	54		
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>		
<b>Psi</b>	6	7	9	12	15	17	20	23	26	29	30	33	35		
10 km/h	2100	2305	2515	2925	3340	3750	3920	4090	4325	4560	4675	4910	5025		
30 km/h	1660	1875	2085	2280	2480	2675	2945	3210	3400	3595	3690				
40 km/h			1950	2135	2315	2500	2750	3000	3180	3360	3450				
40 km/h Dual	1195	1455	1715	1900	2085	2270	2455	2640	2800	2955	3035				
50 km/h			1775	1965	2155	2345	2540	2730	2895	3060	3140				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
<b>38</b>	<b>20.8R38 159A8/156B TL</b>	813266	541	1850	837	5506	DW18L		DW16L W16L W18L		825	524	57		
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>
<b>Psi</b>	6	7	9	12	15	17	20	23	26	29	30	33	35	38	41
10 km/h	2550	2810	3065	3585	4100	4615	4895	5175	5495	5815	5910	6095	6190	6380	6565
30 km/h	1820	2015	2205	2525	2910	3290	3655	4015	4180	4350	4430	4595	4680		
40 km/h			2060	2360	2720	3075	3415	3750	3905	4065	4140	4295	4375		
40 km/h Dual			1810	2075	2390	2705	3005	3300	3440	3575	3645	3780	3850		
50 km/h			1875	2150	2475	2800	3110	3415	3555	3700	3770	3910	3980		

\* Refer to the notes at the end of the tables of this range

# MICHELIN AGRIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>38</b>	<b>520/85R38 155A8/155B TL</b>	303668	530	1855	821	5529	<b>1.6</b>	<b>1.8</b>	DD16 DW16A W16A DD18 W18A	825	509	51
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>			
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>			
max 40 km/h FRT				3000	3415	3825	4240	4650				
10 km/h	2650	2850	3050	3450	3850	4250	4625	5000	5535			
30 km/h	1900	2100	2300	2650	3050	3450	3790	4125				
40 km/h			2120	2500	2825	3150	3515	3875				
40 km/h Dual	1540	1705	1865	2200	2485	2770	3090	3410				
50 km/h			2120	2500	2800	3160	3515	3875				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)			
<b>42</b>	<b>480/80R42 156A8/156B TL</b>	404096	494	1858	847	5538	<b>1.6</b>	<b>1.8</b>	DD16 W16A	801	420	55			
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>	<b>30</b>	<b>33</b>	<b>35</b>	<b>38</b>	<b>41</b>
max 40 km/h FRT				2600	2955	3315	3670	4030	4385	4455	4595	4660	4800		
10 km/h	2325	2505	2690	3050	3415	3775	4140	4500	4750	5000	5125	5375	5500	5750	6000
30 km/h	1660	1830	2000	2335	2675	3015	3350	3690	3840	3985	4060	4205	4280		
40 km/h			1850	2170	2490	2810	3130	3450	3590	3725	3795	3930	4000		
40 km/h Dual	1320	1465	1605	1890	2180	2465	2750	3035	3155	3280	3340	3460	3520		
50 km/h			1850	2170	2490	2810	3130	3450	3590	3725	3795	3930	4000		

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>42</b>	<b>520/85R42 157A8/157B TL</b>	122791	539	1945	869	5771	<b>1.6</b>	<b>1.8</b>	DD18 W18A	802	545	59
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>			
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>			
max 40 km/h FRT				3090	3555	4020	4485	4950				
10 km/h	2800	3015	3225	3650	4075	4500	4900	5300	5865			
30 km/h	2000	2180	2360	2800	3175	3550	3965	4375				
40 km/h			2240	2575	2965	3350	3740	4125				
40 km/h Dual	1630	1800	1970	2265	2610	2950	3290	3630				
50 km/h			2240	2575	3000	3350	3740	4125				

\* Refer to the notes at the end of the tables of this range

# MICHELIN AGRIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)				
<b>46</b>	<b>420/80R46 151A8/1488 TL</b>	122770	410	1872	861	5555	DW13	DW12	835	334	51				
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>
<b>Psi</b>	6	7	9	12	15	17	20	23	26	29	30	33	35	38	41
10 km/h	2000	2170	2340	2675	3015	3350	3675	4000	4315	4625	4720	4905	5000	5075	5150
30 km/h	1450	1575	1700	2000	2290	2575	2865	3150	3300	3450	3500	3600	3650		
40 km/h			1600	1850	2140	2430	2665	2900	3075	3250	3300	3400	3450		
40 km/h Dual	1160	1285	1410	1630	1885	2140	2345	2550	2705	2860	2905	2990	3035		
50 km/h			1450	1700	1950	2240	2445	2650	2800	3000	3040	3115	3150		

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)				
<b>46</b>	<b>480/80R46 158A8/1588 TL</b>	637231	499	1948	889	5874	DW16A	DD16 DW16L W16A	834	449	54				
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>
<b>Psi</b>	6	7	9	12	15	17	20	23	26	29	30	33	35	38	41
max 40 km/h FRT				2725	3095	3465	3830	4200	4570	4660	4835	4925	5100		
10 km/h	2475	2675	2875	3275	3675	4075	4475	4875	5125	5375	5500	5755	5880	6130	6380
30 km/h	1770	1940	2110	2445	2785	3125	3460	3800	3990	4175	4270	4455	4550		
40 km/h			1950	2270	2590	2910	3230	3550	3725	3900	3990	4165	4250		
40 km/h Dual	1450	1585	1715	1940	2165	2390	2615	2840	3065	3290	3405	3630	3740		
50 km/h			1950	2270	2590	2910	3230	3550	3725	3900	3990	4165	4250		

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>46</b>	<b>520/85R46 158A8/1558 TL</b>	122780	515	2050	920	6088	DW16A	DW16L W16A DW18L W18L WT16L W18A DW18A	834	581	58
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>		
<b>Psi</b>	6	7	9	12	15	17	20	23	26		
max 40 km/h FRT				3230	3700	4165	4635	5100			
10 km/h	2900	3115	3325	3750	4175	4600	5025	5450	6070		
30 km/h	2090	2295	2500	2910	3320	3730	4140	4550			
40 km/h			2300	2690	3080	3470	3860	4250			
40 km/h Dual	1715	1885	2055	2390	2730	3065	3400	3740			
50 km/h			2120	2470	2820	3175	3525	3875			

\* Refer to the notes at the end of the tables of this range

# MICHELIN AGRIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)				
<b>50</b>	<b>480/80R50 159A8/1598 TL</b>	471947	474	2056	942	6135	DW15A	DW16A		479	56				
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>	<b>30</b>	<b>33</b>	<b>35</b>	<b>38</b>	<b>41</b>
max 40 km/h FRT				2830	3230	3635	4035	4440	4840	4910	5045	5115	5250		
10 km/h	2575	2785	2995	3415	3830	4250	4700	5150	5575	6000	6075	6225	6300	6400	6500
30 km/h	1800	1990	2180	2575	2915	3250	3625	4000	4190	4375	4440	4565	4625		
40 km/h			2060	2360	2720	3075	3415	3750	3940	4125	4190	4315	4375		
40 km/h Dual	1495	1655	1815	2075	2390	2705	3005	3300	3465	3630	3685	3795	3850		
50 km/h			2060	2360	2725	3075	3415	3750	3875	4125	4190	4315	4375		

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)				
<b>50</b>	<b>480/95R50 164A8/1648 TL</b>	491183	515	2175	992	6484	DW16B (A)	DW15B (A)		593	53				
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>2</b>	<b>2.1</b>	<b>2.3</b>	<b>2.4</b>	<b>2.6</b>	<b>2.8</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>29</b>	<b>30</b>	<b>33</b>	<b>35</b>	<b>38</b>	<b>41</b>
max 40 km/h FRT				3320	3760	4205	4645	5090	5530	5610	5765	5845	6000		
10 km/h	2925	3100	3270	3780	4285	4795	5300	5810	6185	6560	6750	7125	7310	7405	7500
30 km/h	2085	2305	2525	2955	3385	3820	4250	4680	4850	5015	5100	5265	5350		
40 km/h			2360	2765	3165	3570	3970	4375	4530	4690	4765	4920	5000		
40 km/h Dual	1720	1900	2080	2435	2790	3140	3495	3850	3990	4125	4195	4330	4400		
50 km/h			2360	2765	3165	3570	3970	4375	4530	4690	4765	4920	5000		

**\*IMPORTANT:**

The inflation pressure must always be appropriate for the load per tire, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (October 2020). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque, use the 30 km/h column.
- When using single tire configuration:
  - add 0.4 bar for use on slopes of more than 20%
  - add 0.4 bar for intense road use exceeding 50% of time on road
- 10 km/h LT (Low Torque) (max speed 10 km/h).
- FRT: Free Rolling Tire