



# MICHELIN MULTIBIB

**EXCELLENT LONGEVITY  
FOR INCREASED MILEAGE**



## FOR TRACTORS UP TO 220 HP

(for high load / torque, use MICHELIN MACHXBIB / AXIOBIB / AXIOBIB 2)



## VERSATILITY

- Great performance in the field & on the road



## PRODUCTIVITY

- High traction to save time & fuel
- Soil protection
- Capable of speeds of up to 65 km/h<sup>(1)</sup>



## SERVICE LIFE

- Deepest tread depth vs 4 main competitors<sup>(2)</sup>



## COMFORT

- Excellent road handling
- Increased ride comfort

(1) When authorised by the laws in force in the country

(2) For 650/65 R42 size

## SIZES

320/65R16 107D TL

320/65R18 109A8/106B TL

340/65R18 113A8/110B TL

420/65R20 125A8/125B TL

440/65R20 128D TL

420/65R24 126D TL

420/65R24 126A8/126B TL

440/65R24 128D TL

480/65R24 133D TL

540/65R24 140D TL

420/65R28 135D TL

440/65R28 131D TL

480/65R28 136D TL

540/65R28 142D TL

540/65R30 143D TL

540/65R34 145D TL

540/65R34 152D TL

600/65R34 151D TL

540/65R38 147D TL

600/65R38 153D TL

650/65R38 157D TL

650/65R42 158D TL

# MICHELIN MULTIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>16</b>	<b>320/65R16 107D TL</b>	494658	300	827	368	2452	W10L		W9		65	29
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>		
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>28</b>		
10 km/h	530	580	630	760	885	1015	1140	1270	1395	1460		
30 km/h	520	570	620	720	820	920	1025	1125				
40 km/h		530	580	680	775	875	975	1070				
50 km/h		510	555	650	745	840	935	1025				
65 km/h		490	535	625	710	800	890	975				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>18</b>	<b>320/65R18 109A8/106B TL</b> <i>XM108</i>	123898	309	875	389	2594	W9		W10	444	64	28
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>	<b>1.9</b>	
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>25</b>	<b>26</b>	<b>28</b>	
10 km/h	400	535	670	805	940	1075	1210	1345	1415	1480	1550	
30 km/h	390	500	610	710	805	905	1000	1100				
40 km/h		460	570	665	755	850	940	1030				
50 km/h		430	520	605	690	780	865	950				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>18</b>	<b>340/65R18 113A8/110B TL</b> <i>XM108</i>	123888	319	911	407	2719	W9		W10 W11	444	77	29
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>	<b>1.9</b>	
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>25</b>	<b>26</b>	<b>28</b>	
10 km/h	450	600	750	900	1050	1200	1355	1505	1580	1655	1730	
30 km/h	440	560	680	790	900	1010	1120	1230				
40 km/h		520	630	735	840	945	1050	1150				
50 km/h		480	580	675	770	870	965	1060				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>20</b>	<b>420/65R20 125A8/125B TL</b> <i>XM108</i>	122702	396	1064	461	3135	W11		W10 W12	664	140	36
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>		
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>25</b>	<b>26</b>		
10 km/h	970	1140	1310	1525	1735	1950	2160	2375	2480			
30 km/h	770	925	1080	1255	1425	1600	1770					
40 km/h		830	1010	1170	1330	1490	1650					
50 km/h		830	1010	1115	1225	1330	1435	1545	1595	1650		

\* Refer to the notes at the end of the tables of this range

# MICHELIN MULTIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>20</b>	<b>440/65R20 128D TL</b>	675464	445	1090	475	3260	W14L		W13 W15L	664	157	44
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>	
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>28</b>	<b>29</b>	
10 km/h	1200	1295	1390	1570	1750	1930	2125	2315	2510	2605	2700	
30 km/h	920	1020	1120	1305	1485	1670	1870	2070				
40 km/h			1070	1245	1415	1590	1780	1970				
40 km/h Dual	770	855	940	1095	1245	1400	1570	1735				
50 km/h			1025	1165	1310	1450	1670	1890				
65 km/h			975	1135	1290	1450	1625	1800				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>24</b>	<b>420/65R24 126D TL</b>	171560	392	1156	508	3416	W12		11 W11 DW12	700	159	38
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>	
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>28</b>	<b>29</b>	
10 km/h	1200	1315	1425	1575	1725	1875	2025	2175	2365	2455	2550	
30 km/h	920	1010	1095	1290	1480	1670	1815	1955				
40 km/h			1040	1225	1410	1590	1725	1860				
50 km/h			1000	1175	1350	1525	1655	1785				
65 km/h			950	1120	1285	1450	1575	1700				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>24</b>	<b>420/65R24 126A8/126B TL</b> <i>XM108</i>	122712	395	1160	507	3425	W11		W10 W12	700	150	37
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.7</b>	<b>1.8</b>		
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>25</b>	<b>26</b>		
10 km/h	990	1170	1350	1570	1785	2005	2225	2440	2550			
30 km/h	790	950	1110	1290	1465	1645	1820					
40 km/h		850	1040	1205	1370	1535	1700					
50 km/h		850	1040	1150	1260	1370	1480	1590	1645	1700		

\* Refer to the notes at the end of the tables of this range

# MICHELIN MULTIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>24</b>	<b>440/65R24 128D TL</b>	426389	439	1187	529	3519	DW14L		DW13 W13 W14L DW15L W15L	703	178	44
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>	
<b>Psi</b>	6	7	9	12	15	17	20	23	26	28	29	
10 km/h	1285	1370	1450	1655	1855	2060	2225	2395	2560	2640	2725	
30 km/h	980	1080	1180	1380	1580	1780	1925	2070				
40 km/h			1130	1320	1510	1700	1835	1970				
40 km/h Dual	820	910	995	1160	1330	1495	1615	1735				
50 km/h			1080	1265	1445	1630	1760	1890				
65 km/h			1030	1205	1375	1550	1675	1800				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>24</b>	<b>480/65R24 133D TL</b>	531721	483	1240	546	3667	DW15L		DW14L W14L W15L	710	218	46
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>	
<b>Psi</b>	6	7	9	12	15	17	20	23	26	28	29	
10 km/h	1450	1575	1700	1920	2140	2360	2560	2755	2955	3050	3150	
30 km/h	1120	1240	1360	1575	1795	2010	2190	2370				
40 km/h			1290	1500	1710	1920	2090	2260				
40 km/h Dual	940	1040	1135	1320	1505	1690	1840	1990				
50 km/h			1240	1440	1640	1840	2000	2160				
65 km/h			1180	1370	1560	1750	1905	2060				

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>24</b>	<b>540/65R24 140D TL</b>	097057	532	1312	573	3873	DW16L		W16L DW18L W18L	710	287	48
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>	
<b>Psi</b>	6	7	9	12	15	17	20	23	26	28	29	
10 km/h	1750	1875	2000	2265	2535	2800	3040	3275	3515	3630	3750	
30 km/h	1360	1485	1610	1885	2165	2440	2660	2880				
40 km/h			1530	1795	2055	2320	2530	2740				
40 km/h Dual	1140	1245	1345	1575	1810	2040	2225	2410				
50 km/h			1470	1725	1975	2230	2430	2630				
65 km/h			1400	1640	1880	2120	2310	2500				

\* Refer to the notes at the end of the tables of this range

# MICHELIN MULTIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)		
<b>28</b>	<b>420/65R28 135D TL</b>	778211	390	1238	558	3680	W11		W12		732	177	44		
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>	<b>2.2</b>	<b>2.4</b>	<b>2.7</b>	<b>2.8</b>
<b>Psi</b>	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
10 km/h	1275	1410	1545	1710	1875	2040	2185	2325	2495	2580	2665	2830	3000	3205	3270
30 km/h	980	1085	1185	1355	1535	1715	1890	2070	2180	2235	2290	2395	2505		
40 km/h			1130	1290	1460	1630	1800	1970	2075	2125	2180	2280	2385		
40 km/h Dual	820	910	995	1160	1330	1495	1615	1735	1825	1870	1920	2010	2100	2230	2275
50 km/h			1030	1240	1405	1565	1725	1890	1990	2040	2090	2190	2290		
65 km/h			1030	1180	1335	1490	1645	1800	1895	1945	1990	2085	2180		

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>28</b>	<b>440/65R28 131D TL</b>	386212	437	1291	579	3833	DW14L		W13 W14L W15L		821	198	43	
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>			
<b>Psi</b>	6	7	9	12	15	17	20	23	26	28	29			
10 km/h	1360	1480	1600	1795	1985	2180	2360	2540	2720	2810	2900			
30 km/h	1060	1155	1250	1465	1685	1900	2070	2240						
40 km/h			1190	1395	1605	1810	1975	2140						
40 km/h Dual	890	970	1045	1230	1410	1595	1740	1885						
50 km/h			1140	1335	1535	1730	1890	2050						
65 km/h			1090	1275	1465	1650	1800	1950						

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim		Tube (Code)	75% internal volume (litres)	Tread depth (mm)	
<b>28</b>	<b>480/65R28 136D TL</b>	897574	476	1339	596	3970	DW15L		DW14L W14L W15L		822	242	45	
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>			
<b>Psi</b>	6	7	9	12	15	17	20	23	26	28	29			
10 km/h	1550	1675	1800	2035	2265	2500	2715	2925	3140	3245	3350			
30 km/h	1180	1310	1440	1690	1940	2190	2385	2580						
40 km/h			1370	1605	1845	2080	2265	2450						
40 km/h Dual	990	1100	1205	1415	1620	1830	1995	2155						
50 km/h			1310	1540	1770	2000	2175	2350						
65 km/h			1250	1465	1685	1900	2070	2240						

\* Refer to the notes at the end of the tables of this range

# MICHELIN MULTIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>28</b>	<b>540/65R28 142D TL</b>	792274	529	1427	630	4223	DW16L	W16L DW18L W18L	822	318	48
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>28</b>	<b>29</b>
10 km/h	1900	2040	2180	2455	2725	3000	3250	3500	3750	3875	4000
30 km/h	1440	1585	1730	2015	2295	2580	2815	3050			
40 km/h			1640	1910	2180	2450	2675	2900			
40 km/h Dual	1205	1325	1445	1680	1920	2155	2355	2550			
50 km/h			1580	1835	2095	2350	2565	2780			
65 km/h			1500	1745	1995	2240	2445	2650			

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>30</b>	<b>540/65R30 143D TL</b>	223153	527	1472	648	4353	DW16L	W16L DW18L W18L	754	333	48
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>28</b>	<b>29</b>
10 km/h	1950	2095	2240	2520	2795	3075	3340	3600	3865	3995	4125
30 km/h	1480	1630	1780	2070	2360	2650	2890	3130			
40 km/h			1700	1975	2245	2520	2750	2980			
40 km/h Dual	1240	1370	1495	1735	1980	2220	2420	2620			
50 km/h			1630	1895	2155	2420	2640	2860			
65 km/h			1550	1800	2050	2300	2515	2725			

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim	Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>34</b>	<b>540/65R34 145D TL</b>	712064	530	1574	693	4655	DW16L	W16L DW18L W18L	704	364	48
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>
<b>Psi</b>	<b>6</b>	<b>7</b>	<b>9</b>	<b>12</b>	<b>15</b>	<b>17</b>	<b>20</b>	<b>23</b>	<b>26</b>	<b>28</b>	<b>29</b>
10 km/h	2060	2210	2360	2655	2955	3250	3530	3815	4095	4235	4375
30 km/h	1560	1730	1900	2225	2555	2880	3110	3340			
40 km/h			1810	2120	2430	2740	2960	3180			
40 km/h Dual	1310	1455	1595	1865	2140	2410	2605	2800			
50 km/h			1730	2030	2330	2630	2840	3050			
65 km/h			1650	1935	2215	2500	2700	2900			

\* Refer to the notes at the end of the tables of this range

# MICHELIN MULTIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)			
<b>34</b>	<b>540/65R34 152D TL</b>	214036	530	1590	709	4716	DW16L		W16L DW18L W18L	704	364	48			
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>	<b>2.2</b>	<b>2.4</b>	<b>2.7</b>	<b>2.8</b>
<b>Psi</b>	6	7	9	12	15	17	20	23	26	28	29	32	35	39	41
10 km/h	2060	2210	2360	2655	2955	3250	3530	3815	4095	4235	4375	4625	4875	5215	5325
30 km/h	1560	1730	1900	2225	2555	2880	3110	3340	3525	3620	3710	3895	4080		
40 km/h				1810	2120	2430	2740	2960	3180	3360	3445	3535	3715	3890	
40 km/h Dual	1310	1455	1595	1865	2140	2410	2605	2800	2955	3035	3110	3265	3420		
50 km/h				1730	2030	2330	2630	2840	3050	3220	3305	3390	3560	3730	
65 km/h				1650	1935	2215	2500	2700	2900	3065	3145	3225	3390	3550	

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>34</b>	<b>600/65R34 151D TL</b>	557189	594	1654	732	4897	DW20B (A)		DW18L W18L	823	464	54
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>	
<b>Psi</b>	6	7	9	12	15	17	20	23	26	28	29	
10 km/h	2430	2615	2800	3160	3515	3875	4195	4515	4830	4990	5150	
30 km/h	1840	2040	2240	2605	2975	3340	3655	3970				
40 km/h				2140	2485	2835	3180	3480	3780			
40 km/h Dual	1540	1715	1885	2190	2495	2800	3065	3325				
50 km/h				2050	2385	2715	3050	3335	3620			
65 km/h				1950	2265	2585	2900	3175	3450			

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>38</b>	<b>540/65R38 147D TL</b>	114518	529	1675	745	4965	DW16L		W16L DW18L W18L	824	394	48
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>	
<b>Psi</b>	6	7	9	12	15	17	20	23	26	28	29	
10 km/h	2180	2340	2500	2815	3135	3450	3745	4040	4330	4480	4625	
30 km/h	1670	1840	2010	2325	2645	2960	3250	3540				
40 km/h				1920	2220	2520	2820	3095	3370			
40 km/h Dual	1400	1545	1690	1955	2215	2480	2725	2965				
50 km/h				1840	2125	2415	2700	2965	3230			
65 km/h				1750	2025	2300	2575	2825	3075			

\* Refer to the notes at the end of the tables of this range

# MICHELIN MULTIBIB

Tire specifications and pressure table (bar &amp; psi). Load per tire in kg\*

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>38</b>	<b>600/65R38 153D TL</b>	228045	595	1768	779	5229	DW20B (A)		DW18L W18L	825	500	53
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>	
<b>Psi</b>	6	7	9	12	15	17	20	23	26	28	29	
10 km/h	2575	2775	2970	3355	3740	4125	4455	4790	5120	5285	5450	
30 km/h	1960	2165	2370	2760	3150	3540	3870		4200			
40 km/h			2260	2630	3000	3370	3685		4000			
40 km/h Dual	1645	1820	1990	2315	2640	2965	3245		3520			
50 km/h			2160	2515	2875	3230	3530		3830			
65 km/h			2060	2400	2735	3075	3365		3650			

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>38</b>	<b>650/65R38 157D TL</b>	292904	646	1819	801	5380	DW20B (A)			825	602	56
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>	
<b>Psi</b>	6	7	9	12	15	17	20	23	26	28	29	
10 km/h	2900	3125	3350	3775	4200	4625	5005	5390	5770	5960	6150	
30 km/h	2190	2420	2650	3090	3530	3970	4355		4740			
40 km/h			2520	2940	3360	3780	4150		4520			
40 km/h Dual	1835	2030	2220	2590	2955	3325	3655		3980			
50 km/h			2420	2820	3220	3620	3975		4330			
65 km/h			2300	2685	3065	3450	3790		4125			

Ø inches	Description	CAI	e mm	D mm	R' mm	RC mm	Recommended Rim		Acceptable Rim	Tube (Code)	75% internal volume (litres)	Tread depth (mm)
<b>42</b>	<b>650/65R42 158D TL</b>	167733	638	1931	858	5722	DW20B (A)			802	647	57
<b>Bar</b>	<b>0.4</b>	<b>0.5</b>	<b>0.6</b>	<b>0.8</b>	<b>1</b>	<b>1.2</b>	<b>1.4</b>	<b>1.6</b>	<b>1.8</b>	<b>1.9</b>	<b>2</b>	
<b>Psi</b>	6	7	9	12	15	17	20	23	26	28	29	
10 km/h	3000	3225	3450	3885	4315	4750	5155	5565	5970	6170	6375	
30 km/h	2300	2545	2790	3260	3730	4200	4545		4890			
40 km/h			2660	3105	3555	4000	4325		4650			
40 km/h Dual	1930	2135	2340	2735	3125	3520	3805		4090			
50 km/h			2550	2975	3405	3830	4145		4460			
65 km/h			2430	2835	3245	3650	3950		4250			

**\*IMPORTANT:**

The inflation pressure must always be appropriate for the load per tire, the speed of travel and the work to be done. Our recommendations above are provided subject to changes made after the date of publication of these tables (October 2020). Technical data is subject to change without prior notice.

- For plowing and other field applications subject to high torque, use the 30 km/h line.
- When using single tire configuration:
  - add 0.4 bar for use on slopes of more than 20%
  - add 0.4 bar for intensive road use exceeding 50% of time on road
- 10 km/h LT (Low Torque) (max speed 10 km/h).